

LIQUID PLASTER SEALER

LIQUID SEALER FOR DRY OR WET PLASTER

LIQUID PLASTER SEALER forms a tight layer that makes it possible to waterproof wet plaster by creating a very thin, smooth, and dry film in just a few minutes. It is ready-to-use and formulated with natural thermoplastic resin.

Applications

Isolation of dry or wet plaster by forming a moisture barrier film.

Shake the bottle before use.

Apply with a brush, cloth, or paint spray gun on a clean surface. PLASTER SEALER leaves a brown film on the surface, making it easy to identify covered areas. Drying occurs within a few seconds to 1 minute, depending on the applied thickness and ambient temperature. Multiple layers can be applied successively if the film is too thin or damaged.

Packaging

PLASTER SEALER is available in a 500 ml bottle, 1 L refill bottle, and 5 L container.

REFERENCES	PACKAGING
IPL 500	500 ML BOTTLE
IPL 001	1 L REFILL BOTTLE
IPL 005	5 L CONTAINER

Storage

We guarantee PLASTER SEALER for 18 months if stored in its original packaging. Keeping the product cool will extend its shelf life. A preliminary application test is recommended to ensure it meets expectations. Keep the container tightly closed, in a dry and well-ventilated place, away from heat sources and direct sunlight.

Hygiene and Safety

Standard safety precautions should be followed when handling PLASTER SEALER. Please refer to the Safety Data Sheet (SDS) for detailed information.

Customs' code

LIQUID PLASTER SEALER

29051100



Characteristics

Aspect:

Fluid brown liquid

Density:

Approx. 0,85

Viscosity:

Approx. 30 mPa.s

Drying time:

1 min