

SILISKIN

SPRAYABLE SOFT-TOUCH SILICONE COATING

Three-component Soft-Touch coating for RTV, HTV and LSR silicones.



Give your silicone parts a soft, slippery and matte finish !



Drastic reduction of CoF



Excellent adhesion to LSR, RTV and HTV silicone surfaces



Improves abrasion resistance



Ideal for surfaces with up to 1000% elongation



Improves printed silicone parts finish



Reduces fouling and dusting

WHY USE SILISKIN COATING ?



- ☒ Soft Touch
- ☒ Slippery
- ☒ Matte finish

Product information



230b Route des Bouveries 26190 Saint-Nazaire-en-Royans France



www.cop-chimie.com



contact@cop-chimie.com



+ 33 (0) 475 487 720

This flyer was designed using the resources of Flaticon.com and printed by Activ' Graphic.

Do not litter

CHARACTERISTICS OF LIQUID PRODUCTS

Aspect	Very fluid and whitish liquid
Viscosity	• Resin: 1500 mPa.s • Hardener: 10 mPa.s • Mix: +/- 200 mPa.s
Mix ratio	1/1/0.3 (resin/hardener/powder)
Pot life	≈36 hours at 20 °C

CHARACTERISTICS OF THE COATING

Aspect	Matte and translucent finish
Elongation of the surface to be coated	>1 000 %
Coefficient of friction	0.9 ¹
Product output	150 to 200 g of liquid product by m ²

¹CoF reduction as a result of support material

PACKAGING

Siliskin coating resin	500 g or 5 kg
Siliskin coating hardener	500 g or 5 kg
Siliskin powder ²	150 g or 1.5 kg

²product only available to Siliskin customers



Technical vidéo

Technical video - Application of Siliskin coating by spraying



230b Route des Bouveries 26190 Saint-Nazaire-en-Royans France



www.cop-chimie.com



contact@cop-chimie.com



+ 33 (0) 475 487 720

This flyer was designed using the resources of Flaticon.com and printed by Activ' Graphic.

Do not litter